



COMMANDO COMBI™

RANGE INTRODUCTION

Commando Combi units offer RCD protection in hazardous environments.

Enclosed in PC and ABS boxes, these units offer protection against high impact and are available in IP44 (Splashproof) or IP67 (Watertight), making Commando Combination units some of the safest products available.

FEATURES & BENEFITS

- High Impact Protection to IK08
- Available in either IP44 (Splashproof) or IP67 (Watertight) options
- Pre-designed, factory built option

HOW TO SPECIFY

An industrial range of IP44 & IP67 ingress protected "Commando" combination units designed to provide RCD protection in hazardous environments. Options must be available for a maximum of three Commando sockets. Products must have outstanding temperature performance and resistance to chemicals to ensure operation in arduous applications. All sockets to have self-cleaning contacts and nickel plated pins to provide resistance to humidity and wear. Terminals to be clearly identified and have terminal screws backed out to provide ease of installation.



Technical Hotline
+44 (0)1268 563720

Commando Combi™

WIRING DEVICES
INGRESS PROTECTED



TOUGH AND IMPACT
RESISTANT TO IK08

OPTIONAL RCD
PROTECTION

LOCKABLE LID

GOOD CHEMICAL
RESISTANCE

IP44 PRE-CONFIGURED SOCKET
OUTLETS (IP67 AVAILABLE UPON
REQUEST CONTACT TECHNICAL
HOTLINE ON +44 (0)1268 563720)

CUSTOM DESIGNED, FACTORY BUILT
OPTION AVAILABLE
CONTACT TECHNICAL HOTLINE
ON +44 (0)1268 563720
SEE PAGE 268.

Socket outlet selection includes 16A, 32A
and 63A angled socket outlets across all
relevant voltages.



IP44 and IP67
waterproof socket and
switchsocket outlets.



Commando Combi™

**IP44
SPLASHPROOF
100 - 130V
50 - 60 HZ**

Socket Outlets

SINGLE
PRE-WIRED WITH
30mA RCD

TWIN
PRE-WIRED WITH
30mA RCD
INDIVIDUALLY PROTECTED

ANGLED
TWIN
SURFACE
PRE-WIRED

Switchsocket Outlet

INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration
Amps Earth



IP44



Amps	Pin. Config-uration	Earth	Socket Outlets	Socket Outlets	Socket Outlets	Switchsocket Outlet
16	2P+E	4	K13413YEL	K73173YEL	K73143YEL	K13309YEL
32	2P+E	4				K13342YEL

Suitable for top entry
2 x 25mm

Suitable for top entry
2 x ø25 / 2 x ø38
bottom entry 3 x 47.5mm

Suitable for top entry
2 x ø25 / 2 x ø38
bottom entry 3 x 47.5mm

Suitable for top entry
2 x ø25

**IP44
SPLASHPROOF
200 - 250V
50 - 60 HZ**

Socket Outlets

SINGLE
PRE-WIRED WITH
30mA RCD

ANGLED
TWIN
SURFACE
PRE-WIRED

Switchsocket Outlet

INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration
Amps Earth



IP44



Amps	Pin. Config-uration	Earth	Socket Outlets	Socket Outlets	Switchsocket Outlet
16	2P+E	6	K73414BLU	K73174BLU	K73310BLU
63	2P+E	6	K73463BLU		K13343BLU

Suitable for top entry
2 x 25mm

Suitable for top entry
2 x ø25 / 2 x ø38
Bottom entry 3 x 47.5mm

Suitable for top entry
2 x 25mm

**IP44
SPLASHPROOF
380 - 415V
50 - 60 HZ**

Socket Outlets

SINGLE
PRE-WIRED WITH
30mA RCD

SINGLE
PRE-WIRED WITH
SINGLE
30mA RCD

Switchsocket Outlet

INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration
Amps Earth



IP44



Amps	Pin. Config-uration	Earth	Socket Outlets	Socket Outlets	Switchsocket Outlet
16	3P+E	6	K13415RED		K13311RED
16	3P+N+E	6	K13416RED		K13312RED
32	3P+E	6	K13434RED		K13344RED
32	3P+N+E	6	K73435RED		K13345RED
63	3P+N+E	6		K73465RED	

16/32A Suitable for top entry
2 x 25mm

Suitable for top entry
2 x ø25 / 2 x ø38
Bottom entry 3 x 47.5mm

Suitable for top entry
2 x 25mm



Technical Hotline
+44 (0)1268 563720

Commando Combi™

WIRING DEVICES
INGRESS PROTECTED

**IP67
WATERTIGHT
100 - 130V
50 - 60 HZ**

Socket Outlet
SINGLE
PRE-WIRED WITH
30mA RCD

**Switchsocket
Outlet**
INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration Earth



Amps	Pin. Config- uration	Earth
16	2P+E	4
32	2P+E	4

K13713YEL
K73718YEL

K13346YEL

Suitable for top entry
2 x ø25

Suitable for top entry
2 x ø25

**IP67
WATERTIGHT
200 - 250V
50 - 60 HZ**

Socket Outlet
SINGLE
PRE-WIRED
WITH
30mA RCD

**Switchsocket
Outlet**
INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration Earth



Amps	Pin. Config- uration	Earth
16	2P+E	6
16	3P+E	9
32	2P+E	6

K73714BLU

K13348BLU

K13733BLU

K13349BLU

Suitable for top entry
2 x ø25

Suitable for top entry
2 x ø25

**IP67
SPLASHPROOF
380 - 415V
50 - 60 HZ**

Socket Outlet
SINGLE
PRE-WIRED WITH
30mA RCD

**Switchsocket
Outlet**
INTERLOCKED
PRE-WIRED WITH
30mA RCD

Pin.
Config-
uration Earth



Amps	Pin. Config- uration	Earth
16	3P+E	6
16	3P+N+E	6
32	3P+E	6
32	3P+N+E	6

K13716RED

K13351RED
K13352RED

K73735RED

K73353RED

Suitable for top entry
2 x ø25

Suitable for top entry
2 x ø25

